


**Vertical Lift Platform Specification**

- Load: 1000kg / 8 persons
- Drive: Direct driven screw and nut
- Speed: 0.15m / sec
- Travel: Maximum travel up to 9m
- Stops: Max 5 stops
- Motor: 2.2kw
- Power: 415v 3ph 50Hz 10A
- Colour: RAL 9010 as standard (alternative RAL colours available)
- Panels: 80mm thick double skin panels
- Panel Infill: Rockwool Infill
- Fire rating: 1hr (60min)

**Builders work Required**

- 1 - Provide a trimmed pit / shaft aperture to the dimensions shown, pit must be smooth level and structurally sound
- 2 - Provide a power supply complete with a lockable isolator
- 3 - Provide secure thresholds for door fixing



**Door Configurations Available**  
(Guides can go on any side)

<p>Premier Platform Lifts www.pfl.ie</p> <p>Premier Platform Lifts County, Mountshannon, Co. Clare, Ireland Tel: +353 (0)61 922 903 Fax: +353 (0)61 922 904 Email: info@pfls.ie Web: www.lifts.ie</p>	<p>TITLE <b>'A' Type Vertical Platform Lift - 1000kg</b></p>	
	<p>DWG NO. <b>1000 - Fire Rated</b></p>	<p>REV <b>A</b></p>
<p>SCALE <b>NTS</b></p>	<p>DATE <b>28/09/06</b></p>	<p>DRAWN <b>RH</b></p>