


LIFT STD SPECIFICATION

Load capacity	300kg
Drive system	Traction Belt
Speed	0.15 m/s
Maximum number of stops	5
Maximum Travel	14.6m
Pit Depth Required	120mm
Headroom Required	2600mm
Power	230V-mono AC – 50Hz
Motor	1.5 kW
Cabin COP	Full height Vertical
Car Controls	One Touch
Landing Controls	One Touch
Cabin Ceiling	LED bar
Cabin Finish	Skin-plate
Door Type	Telescopic
Door Finish	Skin-plate
Communication	Telephone
Structure	Shaft by others
Structure Finish	Built to withstand the loadings issued on job specific drawing.

Options

- LCD Display
- Voice Announcement
- Cabin Mirror
- Handrail
- Auto-dialer
- Numerous Cabin Finishes
- Stainless Steel Cabin/Landing doors
- 120min Fire rated doors

 PREMIER LIFTS www.lifts.ie Premier Lifts, Glean Glas House, Tuamgraney, Co. Clare, Ireland. Tel: 061 922 903 Email: info@lifts.ie Fax: 061 922 904 Web: www.lifts.ie	ECO700 – Shaft by others -1460mm x 1170mm	
	Single Entry/Exit – Telescopic doors	
	DWG NO - 0001	
	REV - A	
SCALE	DATE	DRAWN
NTS	01/12/2017	APG

NOTE THIS DRAWING IS FOR GUIDANCE ONLY AND MUST NOT BE USED AS A PROPER WORKING DRAWING. FOR ENQUIRIES ABOUT THE LIFT PLEASE CONTACT 061 922 903



Premier Lifts, Glean Glas House,
Tuamgraney, Co. Clare, Ireland.
Tel: 061 922 903 Email: info@lifts.ie
Fax: 061 922 904 Web: www.lifts.ie

ECO700 – Shaft by others -1460mm x 1170mm
Single Entry/Exit – Telescopic doors

DWG NO - 0001

REV - A

SCALE
NTS

DATE
11/10/2011

DRAWN
APG