

LIFT STD SPECIFICATION

Load capacity300kgDrive systemTraction BeltSpeed0.15 m/s

Maximum number of stops5Maximum Travel14.6mPit Depth140mmHeadroom2600

Power 230V-mono AC – 50Hz

Motor 1.5 kW

Cabin COP Full height Vertical

Car Controls

Landing Controls

Cabin Ceiling

Cabin Finish

Door Type

Door Finish

Communication

One Touch

LED bar

Skin-plate

Telescopic

Skin-plate

Telephone

Structure Self- Supporting Structure
Structure Finish Steel in RAL 7040, Fully glazed

on 3 sides.

Options

LCD Display

Voice Announcement

Cabin Mirror Handrail Auto-dialer

Numerous Cabin Finishes

Stainless Steel Cabin/Landing doors

120min Fire rated doors

Alternative RAL Finishes to Structure & Doors



Premier Lifts, Glean Glas House, Tuamgraney, Co. Clare, Ireland. Tel: 061 922 903 Email: info@lifts.ie Fax: 061 922 904 Web: www.lifts.ie

ECO700 – Self Supporting Structure –		
1460mm x 1170mm		
Adjacent Entry/Exit – Telescopic doors		
DWG NO - 0006	REV - A	

DWG NO - 0006		REV - A
SCALE	DATE	DRAWN
NTS	01/12/2017	APG