



LIFT STD SPECIFICATION

- Load capacity - 400kg
- Drive system - Traction Belt
- Speed - 0.15 m/s
- Maximum number of stops - 5
- Maximum Travel - 14.6m
- Pit depth - 140mm
- Headroom - 2450mm
- Power - 230V-mono AC – 50Hz
- Motor - 1.5 kW
- Cabin COP - Full height Vertical
- Car Controls - Constant Pressure
- Landing Controls - One Touch
- Cabin Ceiling - LED bar
- Cabin Finish - Skin-plate
- Door Type - Swing
- Door Finish - RAL 7040
- Communication - Telephone

- Structure - Self-Supporting Structure
- Structure Finish - Steel in RAL 7040, Fully glazed on 3 sides.

Options

- LCD Display
- Voice Announcement
- Cabin Mirror
- Handrail
- Auto-dialer
- Numerous Cabin Finishes
- Various door options
- 60min Fire rated doors
- Alternative RAL Finishes to Structure & Doors



Premier Lifts, Glean Glas House,
 Tuamgraney, Co. Clare, Ireland.
 Tel: 061 922 903 Email: info@lifts.ie
 Fax: 061 922 904 Web: www.lifts.ie

ECO600 – Self Supporting Structure –
 1460mm x 1170mm
 Adjacent Entry/Exit – Swing doors

DWG NO - 0012		REV - A
SCALE	DATE	DRAWN
NTS	11/10/2011	APG