


LIFT STD SPECIFICATION

- Load capacity - 250kg
- Drive system - Screw & Nut
- Speed - 0.04 m/s
- Maximum number of stops - 2
- Maximum Travel - 1m
- Pit - Not required (0mm)
- Power - 230V-mono AC – 50Hz 10A
- Motor - 0.6 kW
- Cabin COP - Full height Vertical
- Platform Controls - Constant Pressure
- Landing Controls - Constant Pressure
- Flooring - Aluminium Checker plate
- Carriage Finish - RAL 7040 Papyrus Swing
- Gate Type - RAL 7040 Grey Papyrus
- Gate Finish - N/A
- Communication - Included
- Handrail - Included
- Auto Folding ramp -

Options

- Stainless Steel Finish to all steelwork
- Automatic Gate
- Glass Carriage Walls
- Glass Gate
- Radio frequency landing controls
- Remote post for landing controls
- Alternative RAL Finishes to carriage & gate

 PREMIER LIFTS www.lifts.ie Premier Lifts, Glean Glas House, Tuamgraney, Co. Clare, Ireland. Tel: 061 922 903 Email: info@lifts.ie Fax: 061 922 904 Web: www.lifts.ie	VPL200 – 1400mm x 1120mm		
	Through Entry/Exit		REV - A
	DWG NO - 0062	SCALE	DATE
NTS	APG	10/11/2017	DRAWN