

Hydraulic Cabinet, to be sited within 12 metres of the lift shaft. A 100mm conduit run for cables & hoses needs to be provided.


LIFT STD SPECIFICATION

Load capacity	350kg
Drive system	Hydraulic 2:1 Roped
Speed	0.15 m/s
Maximum number of stops	5
Maximum Travel	9.25m
Pit depth	140mm
Headroom	2600
Power	230V-mono AC – 50Hz
Motor	1.8 kW
Cabin COP	Full height Vertical
Car Controls	One Touch
Landing Controls	One Touch
Cabin Ceiling	LED bar
Cabin Finish	Skin-plate
Door Type	Telescopic
Door Finish	RAL 7040
Communication	Telephone

Structure Self-Supporting Structure
 Structure Finish Steel in RAL 7040, Fully glazed on 3 sides.

Options

- LCD Display
- Voice Announcement
- Cabin Mirror
- Handrail
- Auto-dialer
- Numerous Cabin Finishes
- Stainless Steel Cabin/Landing doors
- 120min Fire rated doors
- Alternative RAL Finishes to Structure & Doors

 PREMIER LIFTS www.lifts.ie	Premier Lifts, Glean Glas House, Tuamgraney, Co. Clare, Ireland. Tel: 061 922 903 Email: info@lifts.ie Fax: 061 922 904 Web: www.lifts.ie	
	VPL500 – Self Supporting Structure – 1460mm x 1170mm Single Entry/Exit – Telescopic doors	
DWG NO - 0016	REV - A	
SCALE	DATE	DRAWN
NTS	14/11/2017	APG